

TRANSGEAR

85W90

HIGH PRESSURE GEAR OIL

A premium multi grade high pressure gear oil for manual transmissions formulated with "extreme pressure" additives to provide the highest power transfer across the full RPM spectrum from your engine to your drivetrain.

SPECIFICATIONS

API GL-5

APPLICATIONS

- Multi grade gear oil for manual transmissions and axle drives
- Passenger cars, vans, light and heavy duty trucks and buses
- Compatible with typical automotive seals and gaskets

KEY ADVANTAGE

- Superior wear protection
- Good thermal stability and resistance to high temperature oxidation
- Outstanding shear stability and frictional properties
- Excellent rust, staining, and corrosion protection
- Extreme pressure additives reduces clutch chatter

PHYSICAL AND CHEMICAL CHARACTERISTICS

PARAMETERS	TEST METHOD	UNIT	RESULTS
Density @ 15°C	ASTM D1298	kg/l	0.900
Viscosity @ 100°C	ASTM D445	cSt	15.0
Viscosity @ 40°C	ASTM D445	cSt	144
Viscosity Index (min)	ASTM D2270	-	105
Pour Point	ASTM D97	°C	-30
Flash Point	ASTM D92	°C	210

The values shown above are typical values at the date of publication, Petrocam Lubricants reserves the right to change these typical values without prior notice.

RECOMMENDED USE

Refer to your vehicle service manual for correct lubricant requirements and service intervals. This product must not be stored at a temperature above 60°C. Exposure to strong sunlight, extreme cold or high temperatures variations must be avoided. All packages must be protected from bad weather conditions.

HEALTH, SAFETY AND ENVIRONMENT

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil into drains or the environment. Dispose to an authorised used oil collection point. This product should not be used for applications other than those for which it is intended.

PACKAGING

1, 5 and 20 litre plastic bottles & 208 litre drums



ENERGY
IN MOTION

www.petrocamlubricants.co.za

6 Western Service Road, Sandton, 2052, South Africa
TEL: +27 11 656 0466
EMAIL: lubricants@petrocam.co.za

PETROCAM
— LUBRICANTS —

A Division of PETROCAM TRADING (Pty) Ltd

www.petrocamlubricants.co.za